Testing interview questions and answers pdf download torrent full hd full

I'm not robot!

```
Software testing is an activity conducted in the software development project. In its essence, software testing aims to answer the question: How does one ensure that the software does what it is
supposed to do and doesn't do what it is not supposed to do? The primary goal behind software testing is to get enough confidence that the software testing is that testing does not improve software quality by itself. Or that a
high amount of testing doesn't mean that the software is high quality. Testing is an indicator of quality, providing crucial feedback to the developers who created the software to take necessary action to fix the problems found in testing. This article provides the frequently asked interview questions by the interviewer for a Software Tester or Quality
Assurance (QA) position. It's divided into three sections based on the skill set of the applicant. The fresher's section includes software testing questions you might get asked for a junior-level position if you are recently graduated from college. The experienced section assumes basic familiarity with the testing process and explores the advanced topics
in testing. This section is suitable for someone with a few years of experience as a tester. In the end, multiple-choice questions are provided to test your understanding of testing. Crack your next tech interview with confidence! Take a free mock interview, get instant? feedback and recommendation Software testing involves evaluating and verifying a
software product's functionality. Basically, it checks whether the software product matches anticipated requirements and makes sure it is defect-free. It can be said that testing enhances the quality of the product by preventing bugs, reducing development costs, and reducing performance issues. You can test the software in many different ways.
Some types of testing are conducted by software developers and some by specialized quality assurance staff. Here are a few different kinds of software testing A programmatic test that tests the internal working of a unit of code, such as a method or a function. Integration Testing
Ensures that multiple components of systems work as expected when they are combined to produce a result. Regression Testing Ensures that existing features/functionality that used to work are not broken due to new code changes. System works as
expected. Smoke Testing A quick test performed to ensure that the software works at the most basic level and doesn't crash when it's started. Its name originates from the hardware testing where you just plug the device and see if smoke comes out. Performance Testing Ensures that the software performs according to the user's expectations by
checking the response time and throughput under specific load and environment. User-Acceptance Testing Ensures the software meets the requirements of the clients or users. This is typically the last step before the software meets the requirements of the clients or users. This is typically the last step before the software meets the requirements of the clients or users. This is typically the last step before the software meets the requirements of the clients or users.
increases. In stress testing, the tester subjects the software under heavy loads, such as a high number of requests or stringent memory conditions to verify if it works well. Usability Testing Measures how usable the software is. This is typically performed with a sample set of end-users, who use the software and provide feedback on how easy or
complicated it is to use the software. Security Testing Now more important than ever. Security testing is crucial for web-based applications or any applications that involve money. Software testing is governed by seven principles: Absence of errors
fallacy: Even if the software is 99% bug-free, it is unusable if it does not conform to the user's requirements. Software needs to be bug-free 99% of the time, and it must also meet all customer requirements. Testing shows the presence of defects in software, but it cannot guarantee that the software is defect-
free. Testing can minimize the number of defects, but it can't remove them all. Exhaustive testing is not possible: The software cannot be tested exhaustively, which means all possible test cases cannot be tested exhaustively, which means all possible test cases cannot be covered. Testing can only be done with a select few test cases, and it's assumed that the software will produce the right output in all cases. Taking
the software through every test case will cost more, take more effort, etc., which makes it impractical. Defect clustering: The majority of defects are typically found in a small number of modules. Pesticide Paradox: It is impossible to find new bugs by re-
running the same test cases over and over again. Thus, updating or adding new test cases is necessary in order to find new bugs. Early testing: Early testing is crucial to finding the defect in the software. In the early stages of SDLC, defects will be detected more easily and at a lower cost. Software testing should start at the initial phase of software.
development, which is the requirement analysis phase. Testing is context-dependent: The testing approach varies depending on its type. For instance, an ed-tech site is tested differently than an Android app. You can download a PDF version of Software Testing
Interview Questions. Download PDF Download PDF Download PDF The dictionary definition of regression is the act of going back to a previous place or state. In software, regression implies that a feature that used to work suddenly stopped working after a developer added a new code or functionality to the software. Regression problems are pervasive in the
software industry, as new features are getting added all the time. Developers don't build these features in isolation, separate from the existing code. Instead, the new code interacts with the legacy code and modifies it in various ways, introducing new changes
may negatively impact a working feature. It's important to keep in mind that even a small change has the potential to cause regression. Regression testing helps ensure that the new code or modifications to the existing code don't break the present behaviour. It allows the tester to verify that the new code plays well with the legacy code. Imagine a
tourist in a foreign city. There are two ways in which they can explore the city. Follow a map, itinerary, or a list of places they should visit Explore randomly, following the streets as they lead them to new places With the first approach, the tourist follows a predetermined plan and executes it. Though they may visit famous spots, they might miss out
on hidden, more exciting places in the city. With the second approach, the tourist wanders around the city and might encounter strange and exotic places that the itinerary would have missed. Both approaches have their pros and cons. A tester is similar to a tourist when they are testing software. They can follow a strict set of test cases and test the
software according to them, with the provided inputs and outputs, or they can explore the software. When a tester doesn't use the test scripts or a predefined test plan and randomly tests the software, it is called exploratory testing. As the name suggests, the tester is exploring the software as an end-user would. It's a form of black-box testing. In
exploratory testing, the tester interacts with the software in whatever manner they want and follows the software's instructions to navigate various paths and functionality. They don't have a strict plan at hand. Exploratory testing primarily focuses on behavioural testing. It is effective for getting familiar with new software features. It also provides a
high-level overview of the system that helps evaluate and quickly learn the software should and shouldn't do, it allows greater flexibility for the tester to discover hidden pathses random, exploratory testing can be powerful in an experienced and skilled tester's hands. As it's performed without any preconceived notions of what software should and shouldn't do, it allows greater flexibility for the tester to discover hidden pathses.
and problems along those paths. End to End testing is the process of testing a software system from start to finish. The tester would, open it, use the application as intended, and verify the behavior. Same for a web
application. There is an important difference between end-to-end testing vs. other forms of testing that are more isolated, such as unit testing. In end-to-end testing, the software is tested along with all its dependencies and integrations, such as unit testing is the process of testing a single
unit of code in an isolated manner. The unit of code can be a method, a class, or a module. Unit testing aims to focus on the smallest building blocks of code to get confidence to combine them later to produce fully functioning software. A unit test invokes the code and verifies the result with the expected result. If the expected and actual outcomes
match, then the unit test passes. Otherwise, it fails. A good unit test has the following characteristics: It should test a single piece of functionality. It is fully automated and repeatable. It should be isolated and shouldn't interact with external dependencies such as network, database, or file system
unless needed. You can use the mocking technique to simulate the external dependencies and isolate the code under test. API stands for Application Programming Interface. It is a means of communication between two software components. An API abstracts the internal workings and complexity of a software program and allows the user of that API
to solely focus on the inputs and outputs required to use it. When building software, developers rarely write software from scratch and make use of other third-party libraries. An API allows two software components to talk to each other by providing an interface that they can understand. Another use of an API is to provide data required by an
application. Let's say you are building a weather application that displays the temperature. Instead of building the technology to collect the temperature yourself, you'd access the API provided by the meteorological institute. A test environment machine
and tries to represent the actual hardware on which the software will run; once it's in production. Whenever a new build of the software is released, the tester moves on to testing new functionality. When software is being tested, the code
coverage measures how much of the program's source code is coverage testing runs in parallel with actual product testing. Using the code coverage testing runs in parallel with actual product testing. Using the pending statements, along with the coverage percentage, is provided at the
end of the final testing. Among the different types of test coverage: This metric measures how many statements in the source code have been successfully executed and tested. Path Coverage: This metric measures how many statements in the source code have been successfully executed and tested. Path Coverage:
This ensures that the tests are conducted on every possible route through a section of the code. Function coverage: It measures how many functions in the source code have been executed and tested at least once. Black-box testing in software testing: In black-box testing in software testing: In black-box testing in software testing in software testing in software testing.
how the software functions on the inside. This is the only limitation of the black-box test. It is used in Acceptance Testing and Unit testing. Grey-
box testing in software testing: A Gray Box Testing technique can be characterized as a combination of a black box as well as a white box testing tructure. It is extremely beneficial to use
automation testing when using the agile model in software testing. It helps in achieving maximum test coverage in a lesser time of the sprint. Test Case: Test Case are a series of actions executed during software development to verify a particular feature or function. A test case consists of test steps, test data, preconditions, and postconditions
designed to verify a specific requirement. Test Scenario: Usually, a test scenario consists of a set of test cases covering the end-to-end functionality of a software application. A test scenario provides a high-level overview of what needs to be tested. Test Scripts: When it comes to software testing, a test script refers to the set of instructions that will be
followed in order to verify that the system under test performs as expected. The document outlines each step to be taken and the expected results. A software to find bugs in it. There are many causes for the bugs—for example, poor design, sloppy
programming, lack of version control, or miscommunication. Throughout developers introduce hundreds or thousands of bugs in the system. The goal of the tester is to uncover those bugs. You can find a bug in many different ways, regardless of your role. When building the software, the software developer might notice the bug in
another module, written by another developer or by themselves. The tester actively tries to find the bugs as part of a routine testing process. Finally, the users could see the bugs when the software is in production. All bugs, no matter how they are found, are recorded into a bug-tracking system. A triage team triages the bugs and assigns a priority to
the bug, and assigns the bug to a software developer to fix it. Once the developer resolves the problem, they check in the code and mark that bug as ready for testing. Once a bug is ready for testing, it goes to the tester, who tests the software to verify if it's indeed fixed. If it is, then it's closed. If not, they assign it to the same developer with a
description of the exact steps to reproduce the bug. Some examples of popular bug-tracking systems include BugZilla, FogBugz, etc. Trivia: The first software bug was discovered by Admiral Grace Hopper, on September 9, 1947. After they opened a malfunctioning piece of hardware, they found an insect stuck in the relay. Image Source: LinkFirst
Software Bug Bugs and errors differ in the following ways: Bugs Errors Software or an application does not work as intended. A bug occurs when the code, which means that the developer
could have misunderstood the requirement or the requirement was not defined correctly, leading to a mistake. The bug is submitted by the testers. Errors are raised by test engineers and developers. Logic bugs, resource bugs, and algorithmic bugs are types of bugs. Syntactic error, error handling error, user interface error,
flow control error, calculation error, and testing error are types of errors. The software is detected before it is deployed in production. The error occurs when the code is unable to be compiled. A test plan is basically a dynamic document monitored and controlled by the testing manager. The success of a testing project totally depends upon a well-
written test plan document that describes software testing scope and activities. It basically serves as a blueprint that outlines the what, when, how, and more of the entire test process. A test plan must include the following details: Test Strategy Test Objective Test Scope Reason for Testing Exit/Suspension Criteria Resource Planning Test
Deliverables. Test report is basically a document that includes a total summary of testing results. It is very much required to reflect testing results and gives an opportunity to estimate testing results. It is very much required to reflect testing results and gives an opportunity to estimate testing results. It is very much required to reflect testing results and gives an opportunity to estimate testing results.
the project and the quality of the product. A test report must include the following details: Test Objective Project Information Defect Test Summary Test deliverables, also known as test artifacts, are basically a list of all of the documents, tools, and other components that are given to the stakeholders of a software project during the SDLC. Test
deliverables are maintained and developed in support of the test. At every phase of SDLC, there are different deliverables as given below: Before Testing Phase Test Data Test Data Test Data Test Traceability Matrix Error logs and execution logs
After testing Phase Test Results/reports Defect Report Installation/ Test procedures guidelines Release notes Different categories of debugging include: Brute force debugging include: Br
following the exact process Improper resource allocation. It ignores the design and implementation details. A user story aims to focus on the value provided to
the end-user instead of the exact inputs they might enter and the expected output. In a user story, the tester creates user personas with real names and characteristics and tries to simulate a real-life interaction with the software. A user story often helps fish out hidden problems that are often not revealed by more formal testing processes. Selenium: a
web browser automation tool that automates the test suites you need to run on a web browser. Protractor: An end-to-end test framework for Angular and Angular and Angular and Angular sol built for the modern
web. Though it's similar to Selenium and Protractor, it's architecturally different from them. Jasmine: This is an open-source JavaScript testing framework for Java and C# programming languages, respectively. A/B testing is the process of testing two
or more different versions of your software with users to assess which performs better. It is a low-risk way of testing to decide the final version of the
feature. Typically, A/B testing is used to test the user experience of different interfaces. This allows the team to quickly gather feedback and test their initial hypothesis. The term defect refers to a system error that prevents the intended action from being accomplished. Testing is most important when it comes to finding defects. Testing needs to
begin early in the development process since defects can be found throughout. As shown in the following figure, defects are divided into three main categories: Wrong: It implies incorrect implementation of requirements. There is a variance between the specifications and what was expected, resulting in this defect. Missing: This indicates that a
specification has not been implemented, or a requirement of the customer has not been properly noted. Extra: In this case, the defect is caused by a requirement incorporated into the product that was not provided by the end-user. SPICE stands for Software Process Improvement and Capability Determination. In the field of software development
processes, SPICE is a standard framework for assessing the efficiency and effectiveness of the development process. IEC (International Electrotechnical Commission) and ISO (International Organization for Standardization) jointly development process. IEC (International Electrotechnical Commission) and ISO (International Electrote
conditions required to invoke them have not been met. As a systematic flaw, it encompasses the entire production process of the software, including all pre-production testing and extended testing. When users perform a particular task in an unusual or rare situation or without the presence of usual scenarios, latent defects are revealed. Masked
Defect: These are the defects that have not yet resulted in a failure since another defect hiden or marked by another defect and remain hidden until the other defect is exposed by the user through a specific operation. There are defects that have not yet resulted in a failure since another defect in a failure since another defect hiden until the other defect hiden or marked by another defect in a failure since another defect hiden until the other 
detected. The term 'sanity testing' refers to a subset of regression testing ensures that the changes made to the code do not adversely affect the system's performance. After the software build is received, a sanity testing is
used to determine whether the build can proceed with further testing. Sanity testing focuses on a smaller section of the application and is a subset of regression testing. The process is undocumented. Sanity testing is often unscripted. In this approach,
limited functionalities are deeply tested. A tester is usually responsible for performing this task. The TestNG framework for Java is an open-source advanced test automation framework that is designed to benefit both testers and developers. The purpose of TestNG is to provide an easy-to-use, readable, structured, maintainable, and user-friendly
environment for automated tests. NG stands for 'Next Generation' in TestNG. The high-end annotations, such as data providers, make cross-browser testing easier since you can test across multiple devices and browsers. Furthermore, the framework has an inbuilt mechanism for handling exceptions that prevent the program from terminating
unexpectedly. Yes, you can skip a particular test method or code by setting the 'enabled' parameter to 'false' in test annotations.@Test(enabled = false). Prioritizing the order of your test methods can be accomplished by defining a priority order. Consequently, the test will execute in accordance with the priority set.Syntax: @Test(priority=2)Example:
Sequence:ScalerMethod1 ScalerMethod2 ScalerMethod3 Object Repository is a collection of web element locators that belong to the Application Under Test (AUT). The QAs maintain all element locators in a separate file known as the property file (. properties) in Selenium. During execution, it serves as a means of identifying objects
between the test script and the application. The following steps can assist in resolving issues during testing: Record: Keep track of any problems that arise and resolve them. Report: Inform higher-level managers of the issues. Control: Establish a process for managing issues. Any software tester's goal is to find out as many bugs and problems in the
system so that the customers don't have to. Hence, a good software tester should have a keen eye for detail. They should know the ins and outs of the software to its limits, to identify bugs that are hard to find with the software's regular use. Having the domain knowledge of the application is
essential. If a tester doesn't understand the specific problems the software is trying to solve, they won't be able to test it thoroughly. A good tester should possess
basic programming skills to think from a developer's perspective, which allows them to notice common programming errors, etc. Communication, both written and verbal, is an essential skill for a tester. A tester will frequently have to interact with both the developers and the management. They should be
able to explain the bugs and problems found during testing to the developers. For each bug found, a good tester should provide a detailed bug report consisting of all the information a developer would need to fix that problem. They should be able to make a good case to the management if they are uncomfortable releasing the software if it contains
unresolved issues. Software Testing Interview Questions for Experienced BVA (Boundary values to create test cases. Input values near the boundary values to create test cases. Input values at the boundary values to create test cases.
cases. If the input falls within the boundary range, then the test is positive; if it falls outside, then it is negative. There are several types of values, including maximum or minimum, inside or outside edge, and typical or error values. Software testing comes into play at different times in different software development methodologies. There are two main
methodologies in software development, namely Waterfall and Agile. In a traditional waterfall software development model, requirements are gathered first. Then a specification document is created based on the document, which drives the design and development of the software.
development life cycle once the complete software system is built. Waterfall Software Development model works in small iterations. You test the software in parallel as it is getting built. The development model works in small iterations. You test the software in parallel as it is getting built. The development model works in small iterations. You test the software in parallel as it is getting built. The development model works in small iterations. You test the software in parallel as it is getting built. The development model works in small iterations.
drives future development. It is impossible to exhaustively test software or prove the absence of errors, no matter how specific your test strategy is. An extensive test that finds hundreds of errors doesn't mean there
are no errors, and the software is perfect. It could easily mean ineffective or incomplete tests. To prove that a program works, you'd have to enter 2610 names, which is
impossible. Since exhaustive testing is not practical, your best strategy as a tester is to pick the test cases that are most likely to find errors. Testing is sufficient when you have enough confidence to release the software and assume it will work as expected. Developers make poor testers. Here are some reasons why: They try to test the code to make
sure that it works, rather than testing all the ways in which it doesn't work. Since they wrote it themselves, developers skip the more sophisticated tests that an experienced tester would perform to break the software.
They follow the happy path to execute the code from start to finish with proper inputs, often not enough to get the confidence to ship software in production. However, it doesn't mean that developers shouldn't test the software in production. However, it doesn't mean that developers shouldn't test the software in production.
hard to find for a tester because they don't always have access to the source code. In short, SDLC (Software Development Life Cycle) enables the development time. A major objective of the SDLC is to produce high-quality software that meets and exceeds the expectations of
customers. SDLC provides a detailed plan with a series of stages, or phases, that encompass their own processes and deliverables. By adhering to the SDLC, development, testing has its life cycle. During the testing, a tester goes through the following
activities. Understand the requirements: Before testing software or a feature, the tester must first understand what it is supposed to do. If they don't know how the software is supposed to work, they can create a test
plan. It includes the scope of testing, i.e., part of software under test and objectives for testing documentation, estimating the test, such as creating documentation, estimating the test, such as creating documentation, estimating the test, such as creating documentation, estimating the test. Prepare a test environment: The
development happens in a development environment, i.e., on a developer's computer that might not represent the actual environment that the software will run in production. A tester prepares an environment that the software will run in production. A tester prepares an environment that might not represent the actual environment that the software will run in production. A tester prepares an environment that might not represent the actual environment that the software will run in production. A tester prepares an environment that the software will run in production. A tester prepares an environment that the software will run in production. A tester prepares an environment that the software will run in production. A tester prepares an environment with the test data that might not represent the actual environment with the software will run in production. A tester prepares an environment with the test data that might not represent the actual environment with the software will run in production. A tester prepares an environment with the software will run in production at the software will run in production. A tester prepares and environment with the software will run in production at the software will run in production. A tester prepares and environment with the software will run in production at the software will run in production
impossible to do exhaustive testing of the software, the tester tries to use realistic test data to give them the confidence that the software will survive the real world if it passes the tests. Test Execution: Once the tester has a complete understanding of the software and has a test environment set up with the test data, they execute the test. Here,
execution means that the tester runs the software or the feature under test and verifies the outcomes. First, the tester finds a bug in the part of the software under test. In this case, they create a test record/bug report. Second, the software
works as expected. Both these events indicate the end of the test cycle. Functional requirements rather than its internal implementation. A functional requirement refers to required behavior in the system, in terms of its input and output. It validates the
software against the functional requirements or the specification, ignoring the non-functional attributes such as performance, usability, and reliability. Functional requirements? Does it solve its intended users' problems? Non-functional testing tests the
system's non-functional requirements, which refer to an attribute or quality of the system explicitly requested by the client. These include performance, security, scalability, and usability, non-functional testing comes after functional testing. It tests the general characteristics unrelated to the functional requirements of the system explicitly requested by the client.
testing ensures that the software is secure, scalable, high-performance, and won't crash under heavy load. During testing, a tester records their observations, findings, and other information useful to the developers or the management. All this data belongs to a test record, also called a bug report. A detailed bug report is an important artifact
produced during testing. It helps the team members with: Understand the problem, Steps to reproduce the problem, The environment and the specific conditions under which it happens, and The resolution if/when the developers fix the problem. Here are a few bits of information that a good bug report should contain. Image Source: Bugzilla Field
Description Title A short headline that summarizes the problem. It shouldn't be too long but just to give just the right information to the reader. It should be specific and accurate. Description The description should answer all the questions that are not explained by the title. It contains a detailed summary of the bug, its severity, and impact, steps to
reproduce, expected results vs. the actual output. Version A lot of time can be wasted in trying to reproduce a bug in the wrong version of the product. Knowing the exact product version A lot of time can be either 'Active', 'Ready for
Testing', or 'Closed'. A bug becomes active when it is found, is ready for testing once the developer fixes it. A tester can mark it closed if the developer fixes it. A tester can mark it closed if the developer fixes it. A tester can mark it closed if the developer fixes it. A tester can mark it closed if the developer fixes it. A tester can mark it closed if the developer fixes it.
include each step one must take to successfully reproduce the problem. Assigned To Name of the developer fixes the bug, they should include the cause for the bug and its resolution. It helps the team in the future when a similar bug resurfaces. For example, here is a picture of
a bug reported on Jira, a popular bug-tracking software. Testing metrics provide a high-level overview to the management or the developers on how the project is going and the next action steps. Here are some of the metrics derived from a record of the tests and failures: Total number of defects found, ordered by their severity Total number of bugs
fixed Total number of problems caused by an error in the source code vs. configuration or external environmental factors Bug find and fix rate over time Bugs by produce/feature area The average time is taken by a bug since it's found and fixed. Total time spent on new feature development vs. time spent on resolving bugs and failures Number of
outstanding bugs before a release Bugs/failures reported by the customers vs. those found by the testers Test-Driven-Development (TDD) is a popular software development technique, first introduced by Kent Beck in his book with the same name, published in 1999. In TDD, a developer working on a feature first writes a failing test, then writes just
enough code to make that test pass. Once they have a passing test, they add another failing test and then write just enough code to pass the failing test. This cycle repeats until the developer has the fully working feature. If the code under the test has external dependencies such as database, files, or network, you can mock them to isolate the
code. Benefits of TDD: Writing tests first forces you to think about the feature you are trying to build, helping you produce better code. As you always have a working set of tests at hand, a failing test indicates that the problem is with the code you just added, reducing the time spent in debugging. Writing tests help the developer to clarify the
requirements and specification. It's challenging to write good tests for a poor set of requirements. It's tough to produce high-quality software unless you can never be sure that your new code, as you already have a test
in place. Selenium is a web browser automation tool that automates the test suits you need to run on a web browsers, e.g., Google Chrome,
Firefox, Safari, etc. You can integrate it with other testing frameworks and tools to build a comprehensive test suite for your software. Selenium Remote Control (RC). Selenium Remote Control (RC). Selenium Remote Control (RC).
as Google Chrome, Mozilla Firefox, Internet Explorer, Safari, etc. Though they all work primarily the same in implementing the software developer to meticulously test the feature on multiple browsers, noticing the subtle
inconsistencies. In cross-browser testing, a software tester launches the web application in all the supported browser and tries to test the same functionality on all of them. They note any unexpected behavior in a browser that doesn't work as expected or looks different; note the behavior and the browser name and version in the test report.
helps the programmer to fix the behavior in all the browsers where it doesn't work as intended. An HTTP request, that is, if the request has been completed or not. A server can send the following five types of responses for an HTTP request. Information (100 - 199)
These status codes provide a temporary response. The response consists of the status line and optional headers and terminates by an empty line. Successfully received, understood, and accepted. Redirect (300 - 399): These status codes indicate further actions the client should take to
satisfy the HTTP request. It can mean that the requested resource may have moved temporarily or permanently. It can also redirect the client who initiated the HTTP request. Server error (500 - 599): The 5XX status code indicates a problem on the server while processing
the request. As the name suggests, automation tool or software like Selenium to write code that performs the following tasks. Automatically run the software. Feed the input data to the system. Examine the output with the expected
outcome. Fail the test if the results don't match. Otherwise, pass the test. Once a test is automated, you can run it as often as you want, to check if any new code has broken it. It enables you to spend your time on other high-value tests, such as exploratory testing that help find bugs that an automated test would miss. Automated testing is beneficial
for repetitive testing with inputs that don't change frequently. Humans get tired and bored from conducting the same tests repeatedly and seeing the same tests repeatedly and seeing the same tests without getting tired or making mistakes than a human feature for the twentieth time. Software is much better at doing repetitive tasks without getting tired or making mistakes than a human feature for the twentieth time.
operator would. The success of Automation testing can be measured using the following criteria: Savings on labor & other costs. Defect Detection Ratio. Automating the execution process and reducing the release time. Though it varies depending on the size and structure of the software development teams, typically, a bug can be assigned the
following types of severities, going from low to high:Low User Interface bugs. Accessibility issues. Medium Leaky abstractions. Software hangs. Users unable to perform a specific action. Boundary conditions. High Crashing under high load. Business logic and/or calculation errors. Any user action that causes the software to crash. Exposing sensitive
user data. Security problems. Loss of data. Test cases for the black box testing are usually written first, followed by test cases for the white box testing. An outline of the design or project plan and the requirements document is required to write black-box testing. An outline of the design or project plan and the requirements document is required to write black-box testing. An outline of the design or project plan and the requirements document is required to write black-box testing.
initial phase of a project isn't the right time to start white box testing because it requires more architecture clarification that isn't available yet. Therefore, white-box test cases are typically written after black-box test cases have been developed. Before you ship the software to the customers, the internal testing team performs alpha testing. Alpha
testing is part of the user acceptance testing. Its goal is to identify bugs before the customers after alpha testing in a real production environment. It is one of the final components of user acceptance testing. Beta testing is
helpful to get feedback from real people using your software in real environments. It's a process of automatically testing a web application, and interacts with the user interface by clicking buttons or links, just like an average user would. The only
difference is that the browser automation can test this very quickly and often, whereas the same test would take a human tester a long time. It's part of automated testing tool that is used to capture actual quality, effort
resources, plan, and time required to capture all the phases of software testing. It only covers the testing phase of the life cycle. Requirement Traceability Matrix (RTM): It is referred to as a document, usually present in the form table, that is used to trace and demonstrate the relationship between the requirements and other artifacts of the project
right from start to end. In simple words, it maps between test cases and customer requirements. V-models, also known as validation or verification models, are SDLC models where the process occurs sequentially in a V-shape. This method consists of associating a testing phase with each corresponding development stage. As each development
activity is accompanied by a testing activity, the next test phase occurs only after the previous phase has been completed. Validation: It is defined as a process that involves dynamic testing of software products by executing the code. This process validates whether we are building the right software that meets that customer's requirement or not. It
involves various activities like system testing, user acceptance testing, user acceptance testing, user acceptance testing, user acceptance testing, and unit testing. Verifications or not. Its ultimate
goal is to ensure the quality of software products, design, architecture, etc. Validation: It is defined as a process that involves dynamic testing of software that meets that customer requirement or not. It involves various activities like system testing, integration
testing, user acceptance testing, and unit testing. Verification: It is defined as a process that involves analyzing the documents. This process verifies whether the software conforms to specification verification. Verification verification verification verification.
checks whether the software meets the specification or not. It is a type of dynamic testing. There is no requirement of executing the code. This process is performed by the QA team to make sure that
the software is built as per the specifications in the SRS document. This process is performed with the involvement of the testing, and desk-checking are some methods that can be used during
validation. It identifies the bugs or errors early in the development process. It can identify the bugs or errors that the verification process. Static testing is a technique in which you test the software without actually executing it. It involves doing
code walkthroughs, code reviews, peer-reviews, or using sophisticated tools such as eslint, StyleCop to perform static analysis of the source code. Static testing is typically performed during software development. In contrast to static testing is typically performed during software testing tests the software when it's executing. The tester runs the software in a test
environment and goes through all the steps involved, entering the inputs and verifying the actual output with the expected result. A confirmation test involves retesting a software product to see if the previously reported bugs have been fixed. A bug is usually reported by testers when a test fails. A new version of the software is released after the
development team fixes the defect. Now that the new software build has been released, the testing team will retest it in order to ensure that the reported bug was actually fixed. It is also referred to as retesting. Defect life cycle, also known as a bug life cycle, is a life cycle of various stages through which a defect goes during its whole lifetime. This
life cycle starts as soon as the defect is discovered or reported by the tester and ends when the defect is resolved and it won't occur again. The defect is resolved and it won't occur again. The defect is discovered or reported by the tester and ends when the tester and
program. If a defect goes unnoticed during the project's initial phase, it is important that the defect is removed during that phase rather than
afterwards. The cost of fixing a defect increases greatly if it is delayed until a later stage in the development cycle. Following is a diagram showing how the cost of a fixing defect increases throughout the phases. It is more expensive to do so during
maintenance. A workbench is a document that explains how an activity should be completed. Often, it is referred to as a step, phase, or task. Workbenches serve as platforms for building and monitoring testers' work structures. Using this method, it is possible to divide tasks into each phase and to reach the customer's expectations using the initial
data. Every workbench has five tasks, which are as follows: Input. Execute. Check. Production output. Rework. When frame and frame index instead. Suppose there are four frame index instead. Suppose there are four frame index instead. Suppose there are four frame index instead.
index attribute. For instance, the first frame would be at index 1, the third frame would be at index 2, and the fourth frame would be at index 3.driver.switchTo().frame(int arg0); You might be asked this tricky question by the interviewer. As an example, he could give you a web page with 20 links, and you would
have to determine which of those 20 links are working and which aren't or are broken. Considering that you must verify the functionality of each link, the workaround is to send HTTP requests to each link, the workaround is to send HTTP requests to each link, the workaround is to send HTTP requests to each link, the workaround is to send HTTP requests to each link, the workaround is to send HTTP requests to each link and analyze the response. It is evident that
the link has been obtained and is working. In the case of any other status, the link is broken. Let's now understand how to do that. As a first step, we must determine the different hyperlinks on the webpage using anchor tags. We can obtain hyperlinks for each tag using the attribute 'href' value and analyze the response received using the driver. get()
method. Conclusion Software testing is an important activity that ensures quality, giving the confidence to release the software development. It also covers important concepts on manual testing and will guide you to master the field of manual testing. However,
testing is only a single component of a good software development strategy. A development team should use high coding standards, best practices, and patterns to reduce the bug count. As a long-term strategy, the best way to improve the testing process is to test frequently, measure the results, gather feedback and use it to get
better. Recommended Resources: References: 1. What testing relates to boundary value analysis? 2. Which of the following is not a testing framework? 3. What is not a valid phase of the STLC (Software Testing Life Cycle)? 5. 6. Which of the following term is not related to
testing? 7. The full form of SPICE is ___. 8. White box technique is also known as- 9. ___ testing is done by going thro' the code. 10. Out of the following? 12. Which of the following is performed with Planning and Documentation? 14. Which of the
following is a tool used for browser automation testing? 15. What type of testing allows the tester to inspect the internal implementation of the software? 16. The software testing? 18. A bug report does not contain: 19. Which of the
following is not a unit testing framework? 20. Smoke testing is conducted to make sure 21. Which step is not part of a software development life cycle (SDLC)? 22. Which of the following activities doesn't represent static testing? 23. When should the tester stop testing the software?
```

